

PRODUCT INFORMATION

Aluminium Raised Reflective Pavement Marker

SB - AW aluminium raised reflective pavement markers created the category over 10 years ago and have led the industry in product innovation, quality, value and service ever since. **SB - AW** aluminium raised reflective pavement markers features the most durability of high-quality aluminum injection molded with abrasion resistant advanced optics to deliver high retained reflectivity.

Product Benefits

- Injection-molded from durable high-impact aluminium
- Advanced optics and modular lens with high reflectivity and durability
- Abrasion resistant coating for enhanced retained reflectivity
- Patented groove bottom ensures aggressive grip to the roadway
- Initial SI values engineered to at least double ASTM standards

Installation Instructions

- 1) Mark and core drill a hole on the pavement surface with 22 mm in diameter by 60 mm deep (0.87" x 2.37").
- 2) Clean the hole by high pressure blower and ensure the hole is dry.
- 3) Install **SB - AW** aluminium raised reflective pavement markers with using either a bitumen or epoxy based adhesive.

Specifications

Lens Area : 168 square millimeters

Dimensions : 100 mm (L) x 100 mm (W) x 18 mm (H)



All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the preceding is made in lieu of all warranties, expressed or implied.

