

PRODUCT INFORMATION



SB-AW Road Patch

SB-AW Road Patch is a patented innovation that promises a quick, effective, and long-lasting method of fixing road crack. The patch forms a waterproof seal that effectively covers cracks on road surfaces. The patch comes with an adhesive backing that bond to asphalt road surfaces. It's designed to be cost effective and keep traffic flowing.



SB-AW Road Patch (AWRRPWZHRP01)

Installation Instructions

Surface Treatment

1. Adhesion such as dust, water, surface impurities etc. must be removed to keep the road dry and clean.
2. Cracks with width between 5-19mm must be cleaned prior to filling with sealant.
3. Cracks with width between 19-55mm must be cleaned as well as leveled with asphalt mixtures prior to filling with sealant.

Asphalt Overlay

1. As soon as the anti-tear road patch is laid, the upper layer should be constructed immediately to avoid rain.
2. After placement of road patch, spread emulsified asphalt onto the scope surface area where asphalt mixture is placed, fine-grained crushed stones or mixed materials can be laid on the patch later.
3. The thickness of the hot asphalt mixture laid on the anti-cracking patch should be greater than 40mm.

Environment Condition

1. Should only apply when the surface temperature is equal and/or greater than 21°.
2. Using warm fire to heat anti-cracking tape is recommended if surface temperature is lower than 10° to ensure flatness, no wrinkles, and no warped edges.
3. In the event of overlap during the laying process, an overlap length 50mm should not exceed more than two layers overlap.
4. It is recommended to roll 2-3 times with a rubber roller after laying the anti-cracking tape.
5. Vehicles can pass after the laying process. The interval between such laying with the upper layer should not exceed 24 hours.

Specifications

Material: PP (Polypropylene)

Colour: Black

Size: 20cm, 25cm, 33cm, 50cm

Feature:

1. Highly effective and durable
2. Resistant to high temperature
3. Easy to use and fast to complete
4. Last-long to waterproof
5. Easy to use and fast to complete

NOTE: For more information on size, colour and materials, please contact us today!

All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the preceding is made in lieu of all warranties, expressed or implied.

